

# Multi-Converter Chassis

## 10 slots Converter Chassis

- Support 10/100Base-TX to 100Base-FX Module and Gigabit Copper to Gigabit Fiber Module
- Hot swap for Chassis
- Redundant power design for Chassis



### OVERVIEW

Lantech Multi-Converter Chassis provides not only 10 independent converter slots, but also one optional extra redundant power supply. There are various modules to satisfy the demand of users, which include Fiber converter series (with LLF function) and Gigabit

converter series. All the converters and redundant power supply supports plug-and-play and hot-swappable features which allow user to plug or pull out the converters/ redundant power supply without rebooting the chassis.

### FEATURES & BENEFITS

- Chassis with 10 Slots for media converter and Gigabit Copper to Gigabit Fiber Module
- Hot swap for Chassis
- Redundant power design for Chassis
- Support 10/100Base-TX to 100Base-FX Module
- Rack-mount installation

### SPECIFICATION

Hardware Specification			
Power	Chassis Cabinet: AC 90~240 VAC, 50/60 HZ, 90w*2	Operational Humidity	10% to 90% (Non-condensing)
Dimension	440mm x 266mm x 133 mm (3U, 19")	EMI & safety	FCC Class A, CE
Operation Temperature	0°C to 45°C (32°F to 113°F)	Warranty	2 years

### ORDERING INFORMATION

- **Multi-Converter Chassis.....P/N: 8420-005**  
10 Slots Converter Chassis + 1 Redundant Power Supply
- **Redundant Power Supply.....P/N: EOTH000680**  
Redundant Power Supply for 10 slots Converter Chassis

Lantech Communications Global Inc.

www.lantechcom.tw  
info@lantechcom.tw

© 2009 Copyright Lantech Communications Global Inc. all rights reserved.  
The revise authority rights of product specifications belong to Lantech Communications Global Inc.  
Lantech may make changes to specification and product descriptions at anytime, without notice.