


## T(P)ES-L5208MGFA

8 10/100TX + 2 1G/2.5G Fiber Q-ODC OM3 (w/8 PoE) EN50155  
OS3 Managed Ethernet Switch; WVI / 24VI / 24TVI input



### OVERVIEW

Lantech T(P)ES-L5208MGFA is a high performance OS3 Ethernet switch with 8 10/100TX + 2 1G/2.5G Fiber Q-ODC OM3. PoE model has 8 PoE 802.3af/at ports which provides advanced security function for network aggregation deployment.

#### **Up to 8 PoE at/af ports w/advanced PoE management and PoE galvanic isolation**

Compliant with 802.3af/at standard, the PoE model is able to feed each PoE port up to 30 Watt at each PoE port for various IP PD devices. It supports advanced PoE management including PoE detection and scheduling. PoE detection can detect if the connected PD hangs then restart the PD; PoE scheduling is to allow pre-set power feeding schedule upon routine time table. Each PoE ports can be Enabled/disabled, get the voltage, current, Watt, and temperature info displayed on WebUI.

PoE galvanic isolation up to 1.5KVDC to provide power input to PoE Ethernet ports insulation prevents cabling and grounding incidents from damaging the Ethernet switch itself.

#### **Lantech OS3 Platform with complete L2 management and upgradable optional L3 & communication protocols**

The switch runs Lantech OS3 platform which is powerful with complete Layer 2 management features and optional upgradable for future expansion, such as Layer 3 Lite, Layer 3, IEC61375-2-5 (ETBN), etc. To learn more about the Lantech OS3 Platform, please refer to [Lantech OS3/OS4 Software Datasheet](#)

#### **Enhanced cybersecurity features with IEC 62443-4-1 certification**

Lantech OS3 platform is designed with high standard of cybersecurity to prevent the threats from network attack such as DDoS attacks. To ensure the safety and reliability of communication networks, Lantech develops our products under strict international security standard and is certified with IEC 62443-4-1 network security standard. To learn

more about Lantech cybersecurity software solution, please refer to [Lantech OS3/OS4 Software Datasheet](#)

#### ***Miss-wiring avoidance, node failure protection, Loop protection***

The switch also embedded several features for strong and reliable network protection in an easy and intuitive way. When the pre-set ring configuration failed or looped by miss-wiring, the switch being able to alert with the LED indicator and disable ring automatically. Node failure protection ensures the switches in a ring to survive after power breakout is back. The status can be shown in NMS when each switch is back. Loop protection is also available to prevent the generation of broadcast storm when a dumb switch is inserted in a closed loop connection.

#### ***User friendly GUI, Auto topology drawing, Enhanced Environmental Monitoring***

The user-friendly UI, innovative auto topology drawing and topology demo makes the switch much easier to get hands-on. The complete CLI enables professional engineer to configure setting by command line. It supports enhanced environmental monitoring for actual input voltage, current, ambient temperature and total power load.

#### ***Built-in IEC 61375-3-4 ECN (Ethernet Consist Network) to work with IEC61375-2-5 TBN***

Lantech OS3 Ethernet switches comply with IEC 61375-3-4 (ECN) standard. The support of Ethernet Consist Network allows interconnection between end devices located in single consist of train and interoperability with IEC61375-2-5 (TBN).

#### ***Editable configuration file; USB port for import/export configuration***

The configuration file of the switch can be imported and edited with word processor for the following switches to configure with ease. The USB port can import/export the configuration from/to USB dongle and also to upgrade firmware from USB dongle. TFTP/HTTP firmware upgrade is supported.

#### ***Event log & message; 2DI + 2DO; Factory default pin***

The switch provides 2DI and 2DO. When disconnection of the specific port was detected; DO will activate the signal LED to alarm. DI can integrate the sensors for events and DO will trigger the outside alarm and switch will send alert information to IP network with email and traps. The factory reset pin can restore the setting back to factory default.


#### ***Dual WVI / 24VI / 24TVI input with max PoE budget and Inrush current protection***

The switch accept 16.8~137.5VDC (WVI model) ; 9~36VDC (24VI model) ; 16.8~56VDC (24TVI model) dual input with Ethernet and PoE galvanic isolation and PoE model can feed 54V output for PoE feeding with 80W budget. The inrush current on initial power up can be limited lower than 10 x nominal current.

#### ***EN50155, EN45545-2; EN61373 compliance; Rugged design with high ESD protection***

The switch is designed to meet with critical network environment with IP54/IP67 aluminum enclosure and M12 connectors for water proof. The switch passed serious tests under extensive Industrial EMI and Safety standards. With EN45545-2 Fire & Smoke and EN50155 verification, it is best switch for railway on-board/track side, vehicle, and mining applications. For more usage flexibilities, the switch supports wide operating temperature from -40°C to 70°C (85°C operation for 10min), which is compliant with the EN50155 Operating Temperature Range Requirement Class OT4.

**DIMENSIONS (unit=mm)**



**SPECIFICATIONS**

**Hardware Specification**

|                     |   |   |
|---------------------|---|---|
| Standards           | IEEE802.3 10Base-T Ethernet<br>IEEE802.3u 100Base-TX<br>IEEE802.3ab 1000Base-T<br>IEEE802.3x Flow Control and Back Pressure<br>IEEE802.3ad Port trunk with LACP<br>IEEE802.1d Spanning Tree<br>IEEE802.1w Rapid Spanning Tree<br>IEEE802.1s Multiple Spanning Tree<br>IEEE802.3ad Link Aggregation Control Protocol (LACP)<br>IEEE802.1AB Link Layer Discovery Protocol (LLDP)<br>IEEE802.1X User Authentication (Radius)<br>IEEE802.1p Class of Service<br>IEEE802.1Q VLAN Tag<br>IEEE802.3at/af Power over Ethernet | 1G/2.5G fiber: Link/Act (Orange)<br>PoE : Link/Act (Green) (PoE model)  |
| Switch Architecture | Back-plane (Switching Fabric): 11.6Gbps   | DI/DO<br>2 Digital Input (DI) :<br>Level 0: -30~2V / Level 1: 10~30V<br>Max. input current:8mA<br>2 Digital Output(DO): Open collector to 80 VDC, 50mA  |
| Mac Address         | 16K MAC address table   | Operating Humidity<br>5% ~ 95% (Non-condensing)   |
| Jumbo frame         | 10KB  | Operating Temperature<br>-40°C~70°C / -40°F~158°F (85°C operation for 10min.)   |
| Connectors          | 10/100TX: 8 x M12 4-pole D-coded with Auto MDI/MDI-X function<br>1G/2.5G Dual Speed Fiber: 2 x Q-ODC OM3 connector for single-mode or multi-mode type fiber cable<br>Power Input connector: 1 x M12 4-pole Male A-coded<br>Reset/Console/USB : 1 x M12 8-pole A-coded<br>DIDO: 1 x M12 5-pole A-coded   | Storage Temperature<br>-40°C~85°C / -40°F~185°F   |
| Network Cable       | 10Base-T: 4-pair STP Cat3 cable<br>100Base-TX: 4-pair STP Cat3/5 cable<br>1000Base-T: 4-pair STP Cat5/5e cable;<br>2.5G Copper: 4-pair STP Cat5e cable<br><br><b>1G/2.5G fiber:</b><br>Multi-mode: 0 to 300 m, 850 nm (62.5/125 μm);<br>Single-mode: 0 to 2 km, 1310 nm (9/125 μm)  | Power Supply<br>Dual DC input<br>16.8~137.5VDC (WV1 model) ;<br>9~36VDC (24V1 model) ;<br>16.8~56VDC (24TV1 model)  |
| LED                 | Per unit: Power 1 (Green), Power 2 (Green), FAULT (Red); RM(Green)<br>10/100TX Ethernet port: Link/Activity (Green)   | PoE Budget (PoE model)<br>80W@24VDC<br>Higher PoE budget can be applied upon request. **  |
|                     |   | PoE pin assignment (PoE model)<br>M12 port #1~#8 (-8 model) ; support IEEE 802.3at/af End-point, Alternative A mode   |
|                     |   | Power Consumption<br>max. 28.9W exclude PoE load  |
|                     |   | Dimensions<br>IP54/IP67 model: Aluminum case<br>235mm(W)x195mm(H)x96.2mm(D)   |
|                     |   | Weight<br>2.65kgs   |
|                     |   | Installation<br>Wall Mount Design   |
|                     |   | EMI & EMS<br>FCC Part 15 Class A,<br>IEC/EN61000-6-2<br>CE EN55032 Class A<br>CE EN55024<br>CE EN61000-4-2 (ESD) Level 3<br>CE EN61000-4-3 (RS) Level 3<br>CE EN61000-4-4 (EFT) Level 3<br>CE EN61000-4-5 ED3 (Surge) Level 3<br>CE EN61000-4-6 (CS) Level 3<br>CE EN61000-4-8 (Magnetic field) Level 3 |

|                   |   |
|-------------------|---|
| Verifications     | EN50155/EN50121-3-2/EN50121-4/IEC61373;<br>EN45545-1, EN 45545-2 Fire & Smoke<br>verification |
| Stability Testing | EN61373 (Shock and Vibration)   |
| MTBF              | TBC (standards: IEC 62380)  |
| Warranty          | 5 years   |

| Software Specification  |   |
|-------------------------|---|
| Lantech OS3<br>Platform | <a href="#">Download Software Datasheet</a> |
|                         | *Future release<br>**Optional               |

## ORDERING INFORMATION

All model packages include M12 caps. For Coating add -C to Model Names.

- **TPES-L5208MGFA-8-QMM-54-WVI.....P/N: 8361-625**  
8 10/100TX + 2 1G/2.5G Fiber Multimode Q-ODC 300M; w/8 PoE at/af EN50155 OS3 Managed Ethernet Switch ;  
16.8V~137.5VDC dual input ; -40°C to 70°C /-40F~158F ; IP54 housing w/ PoE galvanic isolation
- **TPES-L5208MGFA-8-QSM-54-WVI.....P/N: 8361-6251**  
8 10/100TX + 2 1G/2.5G Fiber Single mode Q-ODC 2KM; w/8 PoE at/af EN50155 OS3 Managed Ethernet Switch ;  
16.8V~137.5VDC dual input ; -40°C to 70°C /-40F~158F ; IP54 housing w/ PoE galvanic isolation
- **TES-L5208MGFA-QMM-54-WVI.....P/N: 8361-6252**  
8 10/100TX + 2 1G/2.5G Fiber Multimode Q-ODC 300M; EN50155 OS3 Managed Ethernet Switch ; 16.8V~137.5VDC dual  
input ; -40°C to 70°C /-40F~158F ; IP54 housing w/ galvanic isolation
- **TES-L5208MGFA-QSM-54-WVI.....P/N: 8361-6253**  
8 10/100TX + 2 1G/2.5G Fiber Single mode Q-ODC 2KM; EN50155 OS3 Managed Ethernet Switch ; 16.8V~137.5VDC dual  
input ; -40°C to 70°C /-40F~158F ; IP54 housing w/ galvanic isolation
- **TPES-L5208MGFA-8-QMM-67-WVI.....P/N: 8361-6254**  
8 10/100TX + 2 1G/2.5G Fiber Multimode Q-ODC 300M; w/8 PoE at/af EN50155 OS3 Managed Ethernet Switch ;  
16.8V~137.5VDC dual input ; -40°C to 70°C /-40F~158F ; IP67 housing w/ PoE galvanic isolation
- **TPES-L5208MGFA-8-QSM-67-WVI.....P/N: 8361-6255**  
8 10/100TX + 2 1G/2.5G Fiber Single mode Q-ODC 2KM; w/8 PoE at/af EN50155 OS3 Managed Ethernet Switch ;  
16.8V~137.5VDC dual input ; -40°C to 70°C /-40F~158F ; IP67 housing w/ PoE galvanic isolation
- **TES-L5208MGFA-QMM-67-WVI.....P/N: 8361-6256**  
8 10/100TX + 2 1G/2.5G Fiber Multimode Q-ODC 300M; EN50155 OS3 Managed Ethernet Switch ; 16.8V~137.5VDC dual  
input ; -40°C to 70°C /-40F~158F ; IP67 housing w/ galvanic isolation
- **TES-L5208MGFA-QSM-67-WVI.....P/N: 8361-6257**  
8 10/100TX + 2 1G/2.5G Fiber Single mode Q-ODC 2KM; EN50155 OS3 Managed Ethernet Switch ; 16.8V~137.5VDC dual  
input ; -40°C to 70°C /-40F~158F ; IP67 housing w/ galvanic isolation
- **TPES-L5208MGFA-8-QMM-54-24VI.....P/N: 8361-62501**  
8 10/100TX + 2 1G/2.5G Fiber Multimode Q-ODC 300M; w/8 PoE at/af EN50155 OS3 Managed Ethernet Switch ; 9V~36VDC  
dual input ; -40°C to 70°C /-40F~158F ; IP54 housing w/ PoE galvanic isolation
- **TPES-L5208MGFA-8-QSM-54-24VI.....P/N: 8361-62511**  
8 10/100TX + 2 1G/2.5G Fiber Single mode Q-ODC 2KM; w/8 PoE at/af EN50155 OS3 Managed Ethernet Switch ;  
9V~36VDC dual input ; -40°C to 70°C /-40F~158F ; IP54 housing w/ PoE galvanic isolation
- **TES-L5208MGFA-QMM-54-24VI.....P/N: 8361-62521**  
8 10/100TX + 2 1G/2.5G Fiber Multimode Q-ODC 300M; EN50155 OS3 Managed Ethernet Switch ; 9V~36VDC dual input ; -  
40°C to 70°C /-40F~158F ; IP54 housing w/ galvanic isolation
- **TES-L5208MGFA-QSM-54-24VI.....P/N: 8361-62531**  
8 10/100TX + 2 1G/2.5G Fiber Single mode Q-ODC 2KM; EN50155 OS3 Managed Ethernet Switch ; 9V~36VDC dual input ; -  
40°C to 70°C /-40F~158F ; IP54 housing w/ galvanic isolation
- **TPES-L5208MGFA-8-QMM-67-24VI.....P/N: 8361-62541**  
8 10/100TX + 2 1G/2.5G Fiber Multimode Q-ODC 300M; w/8 PoE at/af EN50155 OS3 Managed Ethernet Switch ; 9V~36VDC  
dual input ; -40°C to 70°C /-40F~158F ; IP67 housing w/ PoE galvanic isolation
- **TPES-L5208MGFA-8-QSM-67-24VI.....P/N: 8361-62551**  
8 10/100TX + 2 1G/2.5G Fiber Single mode Q-ODC 2KM; w/8 PoE at/af EN50155 OS3 Managed Ethernet Switch ;  
9V~36VDC dual input ; -40°C to 70°C /-40F~158F ; IP67 housing w/ PoE galvanic isolation
- **TES-L5208MGFA-QMM-67-24VI.....P/N: 8361-62561**  
8 10/100TX + 2 1G/2.5G Fiber Multimode Q-ODC 300M; EN50155 OS3 Managed Ethernet Switch ; 9V~36VDC dual input ; -  
40°C to 70°C /-40F~158F ; IP67 housing w/ galvanic isolation
- **TES-L5208MGFA-QSM-67-24VI.....P/N: 8361-62571**  
8 10/100TX + 2 1G/2.5G Fiber Single mode Q-ODC 2KM; EN50155 OS3 Managed Ethernet Switch ; 9V~36VDC dual input ; -  
40°C to 70°C /-40F~158F ; IP67 housing w/ galvanic isolation
- **TPES-L5208MGFA-8-QMM-54-24TVI.....P/N: 8361-62502**  
8 10/100TX + 2 1G/2.5G Fiber Multimode Q-ODC 300M; w/8 PoE at/af EN50155 OS3 Managed Ethernet Switch ;  
16.8V~56VDC dual input ; -40°C to 70°C /-40F~158F ; IP54 housing w/ PoE galvanic isolation
- **TPES-L5208MGFA-8-QSM-54-24TVI.....P/N: 8361-62512**  
8 10/100TX + 2 1G/2.5G Fiber Single mode Q-ODC 2KM; w/8 PoE at/af EN50155 OS3 Managed Ethernet Switch ;  
16.8V~56VDC dual input ; -40°C to 70°C /-40F~158F ; IP54 housing w/ PoE galvanic isolation
- **TES-L5208MGFA-QMM-54-24TVI.....P/N: 8361-62522**

- 8 10/100TX + 2 1G/2.5G Fiber Multimode Q-ODC 300M; EN50155 OS3 Managed Ethernet Switch ; 16.8V~56VDC dual input ; -40°C to 70°C /-40F~158F ; IP54 housing w/ galvanic isolation
- **TES-L5208MGFA-QSM-54-24TVI.....P/N: 8361-62532**  
8 10/100TX + 2 1G/2.5G Fiber Single mode Q-ODC 2KM; EN50155 OS3 Managed Ethernet Switch ; 16.8V~56VDC dual input ; -40°C to 70°C /-40F~158F ; IP54 housing w/ galvanic isolation
- **TPES-L5208MGFA-8-QMM-67-24TVI.....P/N: 8361-62542**  
8 10/100TX + 2 1G/2.5G Fiber Multimode Q-ODC 300M; w/8 PoE at/af EN50155 OS3 Managed Ethernet Switch ; 16.8V~56VDC dual input ; -40°C to 70°C /-40F~158F ; IP67 housing w/ PoE galvanic isolation
- **TPES-L5208MGFA-8-QSM-67-24TVI.....P/N: 8361-62552**  
8 10/100TX + 2 1G/2.5G Fiber Single mode Q-ODC 2KM; w/8 PoE at/af EN50155 OS3 Managed Ethernet Switch ; 16.8V~56VDC dual input ; -40°C to 70°C /-40F~158F ; IP67 housing w/ PoE galvanic isolation
- **TES-L5208MGFA-QMM-67-24TVI.....P/N: 8361-62562**  
8 10/100TX + 2 1G/2.5G Fiber Multimode Q-ODC 300M; EN50155 OS3 Managed Ethernet Switch ; 16.8V~56VDC dual input ; -40°C to 70°C /-40F~158F ; IP67 housing w/ galvanic isolation
- **TES-L5208MGFA-QSM-67-24TVI.....P/N: 8361-62572**  
8 10/100TX + 2 1G/2.5G Fiber Single mode Q-ODC 2KM; EN50155 OS3 Managed Ethernet Switch ; 16.8V~56VDC dual input ; -40°C to 70°C /-40F~158F ; IP67 housing w/ galvanic isolation

## OPTIONAL ACCESSORIES

### Software package

Please refer to the [software datasheet](#)

### M12 Connector & Cable

#### Connector

- **ECONM12-04A(F)-C-180** 4 pin M12 (Female) A-coded 180 degree crimp type connector for power supply
- **ECONM12-08A(M)-180** 8 pin M12 (Male) A-coded 180 degree crimp type connector for reset/console/USB
- **ECONM12-05A(M)-C-180** 5 pin M12 (Male) A-coded 180 degree crimp type connector for DI/DO
- **ECONM12-08X(M)-SPEEDCON** 8 pin M12 (Male) X-coded 180 degree crimp type connector for data, Ethernet CAT6A (10G), shielded, SPEEDCON

#### Cable

- **ECONM12-4P(F)1.5M CABLE** 4 pin M12 (Female) A-coded 90 degree cable for power supply, 150cm
- **ECONM12-08M2-CONSOLE** 8 pin M12 (Male) A-coded 180 degree to RS232 cable for console, 150cm
- **ECABM12X83MSTP** 8 pin M12 (Male) X-coded 180 degree RJ45 STP cable for data, shielded, 300cm
- **ECABM002-QOP2-3.0-MM-OM3** Q-ODC 2 plug/LC multi-mode fiber, MM-OM3, 300cm
- **ECABM002-QOP2-3.0-SM-OS2** Q-ODC 2 plug/LC single-mode fiber, SM-OS2, 300cm

#### Others

- **M12 to USB interface adapter** 8 pin M12 (Male) A-coded 180 degree M12 to USB 2.0 interface adapter, 8cm
- **USB 2.0 Ethernet Adapter** USB 2.0 to RJ45 Ethernet Adapter
- **ECONM12-08(M) TO DB9+USB2.0-1.5M CABLE** 8 pin M12 (Male) A-coded 180 degree M12 to USB2.0 to DB9 (Female) cable, 150cm

**Lantech Communications Global Inc.**  
www.lantechcom.tw  
info@lantechcom.tw

© 2023 Copyright Lantech Communications Global Inc. all rights reserved.  
The revise authority rights of product specifications belong to Lantech Communications Global Inc.  
In a continuing effort to improve and advance technology, product specifications are subject to change without notice.