

## T(P)GS-R6608XT

8 10/100/1000T + 6 10G Copper with 8/10/12 PoE, EN50155 OS4 Managed Ethernet Switch; WVI / 24VI / 24TVI input w/ optional dynamic routing, multicast routing, cybersecurity, and hardware NAT



### OVERVIEW

Lantech TPGS-R6608XT is a high performance OS4 Ethernet switch with 8 10/100/1000T + 6 1G/2.5G/5G/10G Copper with 10/12 (incl. 8 copper + 2/4 uplink 10GT copper) or w/8 PoE 802.3af/at ports which provides advanced security function for network aggregation deployment.

#### **Lantech OS4 Platform with complete L2 management and upgradable optional L3 & L3Lite communication protocols incl. dynamic routing, multicast routing, hardware NAT, and PTP**

The switch runs Lantech OS4 platform which is powerful with complete Layer 2 management features and optional upgradable for future expansion, such as Layer 3 Lite, Layer 3, IEC61375-2-5 (ETBN), hardware NAT, PTP, etc. The PTP V2 supports transparent clock and two step processing that improves network time accuracy and precision. To learn more about the Lantech OS4 Platform, please refer to [Lantech OS3/OS4 Software Datasheet](#)

#### **Enhanced cybersecurity features with IEC 62443-4-1, optional IEC 62443-4-2 compliance & built-in DDoS attack protection**

Lantech OS4 platform is designed with high standard of cybersecurity to prevent the threats from network attack such as DDoS attacks. To ensure the safety and reliability of communication networks, Lantech develops our products under strict international security standard and is certified with IEC 62443-4-1 and the switch is also compliant to optional IEC 62443-4-2 standard. To learn more about Lantech cybersecurity software solution, please refer to [Lantech OS3/OS4 Software Datasheet](#)

#### **Up to 8/10/12 PoE at/af ports w/advanced PoE management and PoE galvanic isolation**

Compliant with 802.3af/at standard, the PoE model is able to feed each PoE port up to 30 Watt at each PoE port for various IP PD devices. It supports advanced PoE management including PoE detection and scheduling. PoE detection can detect if the connected PD hangs then restart the PD; PoE scheduling is to allow pre-set power feeding

schedule upon routine time table. Each PoE ports can be Enabled/disabled, get the voltage, current, Watt, and temperature info displayed on WebUI.

PoE galvanic isolation up to 1.5KVDC to provide power input to PoE Ethernet ports insulation prevents cabling and grounding incidents from damaging the Ethernet switch itself.

#### ***Miss-wiring avoidance, node failure protection, Loop protection***

The switch also embedded several features for strong and reliable network protection in an easy and intuitive way. When the pre-set ring configuration failed or looped by miss-wiring, the switch being able to alert with the LED indicator and disable ring automatically. Node failure protection ensures the switches in a ring to survive after power breakout is back. The status can be shown in NMS when each switch is back. Loop protection is also available to prevent the generation of broadcast storm when a dumb switch is inserted in a closed loop connection.

#### ***User friendly GUI, Auto topology drawing, Enhanced Environmental Monitoring***

The user-friendly UI, innovative auto topology drawing and topology demo makes the switch much easier to get hands-on. The complete CLI enables professional engineer to configure setting by command line. It supports enhanced environmental monitoring for actual input voltage, current, ambient temperature and total power load.

#### ***Built-in IEC 61375-3-4 ECN (Ethernet Consist Network) to work with IEC61375-2-5 TBN***

Lantech OS4 Ethernet switches comply with IEC 61375-3-4 (ECN) standard. The support of Ethernet Consist Network allows interconnection between end devices located in single consist of train and interoperability with IEC61375-2-5 (TBN).

#### ***Editable configuration file; USB port for import/export configuration***

The configuration file of the switch can be imported and edited with word processor for the following switches to configure with ease. The USB port can import/export the configuration from/to USB dongle and also to upgrade firmware from USB dongle. TFTP/HTTP firmware upgrade is supported.

#### ***Event log & message; 2DI + 2DO; Factory default pin***

The switch provides 2DI and 2DO. When disconnection of the specific port was detected; DO will activate the signal LED to alarm. DI can integrate the sensors for events and DO will trigger the outside alarm and switch will send alert information to IP network with email and traps. The factory reset pin can restore the setting back to factory default.

#### ***Optional smart bypass protection on dual 10G copper ports***

The bypass relay is set to bypass the switch to the next one when power is off to prevent network disruption. Lantech bypass caters to remain in bypass mode until the switch is completely booting up when power is back to avoid another network lost. Optional smart bypass (Up to two pairs) can be activated when switch encounters power failure. (-BT/-BBT model)

#### ***Dual WVI / 24VI / 24TVI input with max PoE budget and Inrush current protection***


The switch accept 16.8~137.5VDC (WVI model) ; 9~36VDC (24VI model) ; 16.8~56VDC (24TVI model) dual input with Ethernet and PoE galvanic isolation and PoE model can feed 54V output for PoE feeding with 80W budget. The inrush current on initial power up can be limited lower than 10 x nominal current.

#### ***EN50155, EN45545-2; EN61373 compliance; Rugged design with high ESD protection***

The switch is designed to meet with critical network environment with IP21 aluminum enclosure and M12 connectors for water proof. The switch passed serious tests under extensive Industrial EMI and Safety standards. With EN45545-2 Fire & Smoke and EN50155 verification, it is best switch for railway on-board/track side, vehicle, and

mining applications. For more usage flexibilities, the switch supports wide operating temperature from -40°C to 70°C (85°C operation for 10min), which is compliant with the EN50155 Operating Temperature Range Requirement Class OT4.

**DIMENSIONS (unit=mm)**



**SPECIFICATIONS**

**Hardware Specification**

Standards	IEEE802.3 10Base-T Ethernet IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T IEEE802.3ak 10Gbase-T IEEE802.3x Flow Control and Back Pressure IEEE802.3ad Port trunk with LACP IEEE802.1d Spanning Tree IEEE802.1w Rapid Spanning Tree IEEE802.1s Multiple Spanning Tree IEEE802.3ad Link Aggregation Control Protocol (LACP) IEEE802.1AB Link Layer Discovery Protocol (LLDP) IEEE802.1X User Authentication (Radius) IEEE802.1p Class of Service IEEE802.1Q VLAN Tag IEEE802.3at/af Power over Ethernet
Switch Architecture	Back-plane (Switching Fabric): 136Gbps
Mac Address	16K MAC address table
Jumbo frame	10KB
Connectors	10/100/1000T: 8x M12 8-pole X-coded with Auto MDI/MDI-X function

	1G/2.5G/5G/10G Copper: 6x M12 8-pole X-coded Power Input connector: 1 x M12 4-pole Male A-coded Reset/Console/USB : 1 x M12 8-pole A-coded DIDO: 1 x M12 5-pole A-coded
Network Cable	1000Base-T: 4-pair STP Cat5E/6 cable; 10G Copper: 4-pair STP Cat6a/7 cable
LED	Per unit: Power 1 (Green), Power 2 (Green), FAULT (Red); RM(Green) 10/100/1000T Ethernet port: Link/Activity (Green) 1G/2.5G/5G/10G port: speed (1G/2.5G/5G: Yellow; 10G: Orange) PoE : Link/Act (Green)
DI/DO	2 Digital Input (DI) : Level 0: -30~2V / Level 1: 10~30V Max. input current:8mA 2 Digital Output(DO): Open collector to 80 VDC, 50mA
Operating Humidity	5% ~ 95% (Non-condensing)
Operating Temperature	-40°C~70°C / -40°F~158°F (85°C operation for 10min.)

Storage Temperature	-40°C~85°C / -40°F~185°F
Power Supply	Dual DC input 16.8~137.5VDC (WVI model) ; 9~36VDC (24VI model) ; 16.8~56VDC (24TVI model)
PoE Budget (PoE model)	80W@24VDC Higher PoE budget can be applied upon request. **
PoE pin assignment	M12 port #1~#8 (-8 model) M12 port #1~#8, #11~#12 (-10 model) M12 port #1~#8, #11~#14 (-12 model)  Support IEEE 802.3at/af End-point, Alternative A mode
Power Consumption	max. 56.2W exclude PoE load
Dimensions	IP21model: Aluminum case 390mm(W)x195mm(H)x105.3mm(D)
Weight	5.1kgs
Installation	Wall Mount Design
EMI & EMS	FCC Part 15 Class A EN61000-6-2

	EN61000-6-4 CE EN55032 Class A CE EN55024: CE EN61000-4-2 (ESD) Level 3 CE EN61000-4-3 (RS) Level 3 CE EN61000-4-4 (EFT) Level 3 CE EN61000-4-5 ED3 (Surge) Level 3 CE EN61000-4-6 (CS) Level 3 CE N61000-4-8 (Magnetic field) Level 3
Verifications	EN50155/EN50121-3-2/EN50121-4; EN 45545-1, EN 45545-2 Fire & Smoke verification
Stability Testing	EN61373 (Shock and Vibration)
MTBF	325,856 Hrs. (standards: IEC 62380)
Warranty	5 years
Bypass**	Up to two pairs bypass module on 10GT ports to pass to next switch in case of power failure
<b>Software Specification</b>	
Lantech OS4 Platform	<a href="#">Download Software Datasheet</a>

\*Future release  
\*\*Optional

## ORDERING INFORMATION

All model packages include M12 caps. For Coating add -C to Model Name. For optional bypass add -BT (one pair); -BBT (two pairs) to end of model names.

- **TPGS-R6608XT-8-21-WVI.....P/N: 8361-518**  
8 10/100/1000T + 6 10G Copper M12 X-coded w/8 PoE at/af EN50155 OS4 Managed PoE Ethernet Switch ;  
16.8V~137.5VDC dual input ; -40C~70C/-40F~158F ; IP21 housing w/ PoE galvanic isolation
- **TPGS-R6608XT-10-21-WVI.....P/N: 8361-5182**  
8 10/100/1000T + 6 10G Copper M12 X-coded w/10 PoE at/af incl.2 10GT EN50155 OS4 Managed PoE Ethernet Switch ;  
16.8V~137.5VDC dual input ; -40C~70C/-40F~158F ; IP21 housing w/ PoE galvanic isolation
- **TPGS-R6608XT-12-21-WVI.....P/N: 8361-5181**  
8 10/100/1000T + 6 10G Copper M12 X-coded w/12 PoE at/af incl.4 10GT EN50155 OS4 Managed PoE Ethernet Switch ;  
16.8V~137.5VDC dual input ; -40C~70C/-40F~158F ; IP21 housing w/ PoE galvanic isolation
- **TGS-R6608XT-21-WVI.....P/N: 8361-5183**  
8 10/100/1000T + 6 10G Copper M12 X-coded EN50155 OS4 Managed Ethernet Switch ; 16.8V~137.5VDC dual input ; -  
40C~70C/-40F~158F ; IP21 housing w/ galvanic isolation
- **TPGS-R6608XT-8-21-24VI.....P/N: 8361-51801**  
8 10/100/1000T + 6 10G Copper M12 X-coded w/8 PoE at/af EN50155 OS4 Managed PoE Ethernet Switch ; 9V~36VDC dual  
input ; -40C~70C/-40F~158F ; IP21 housing w/ PoE galvanic isolation
- **TPGS-R6608XT-10-21-24VI.....P/N: 8361-51821**  
8 10/100/1000T + 6 10G Copper M12 X-coded w/10 PoE at/af incl.2 10GT EN50155 OS4 Managed PoE Ethernet Switch ;  
9V~36VDC dual input ; -40C~70C/-40F~158F ; IP21 housing w/ PoE galvanic isolation
- **TPGS-R6608XT-12-21-24VI.....P/N: 8361-51811**  
8 10/100/1000T + 6 10G Copper M12 X-coded w/12 PoE at/af incl.4 10GT EN50155 OS4 Managed PoE Ethernet Switch ;  
9V~36VDC dual input ; -40C~70C/-40F~158F ; IP21 housing w/ PoE galvanic isolation
- **TGS-R6608XT-21-24VI.....P/N: 8361-51831**  
8 10/100/1000T + 6 10G Copper M12 X-coded EN50155 OS4 Managed Ethernet Switch ; 9V~36VDC dual input ; -40C~70C/-  
40F~158F ; IP21 housing w/ galvanic isolation
- **TPGS-R6608XT-8-21-24TVI.....P/N: 8361-51802**  
8 10/100/1000T + 6 10G Copper M12 X-coded w/8 PoE at/af EN50155 OS4 Managed PoE Ethernet Switch ; 16.8V~56VDC  
dual input ; -40C~70C/-40F~158F ; IP21 housing w/ PoE galvanic isolation
- **TPGS-R6608XT-10-21-24TVI.....P/N: 8361-51822**  
8 10/100/1000T + 6 10G Copper M12 X-coded w/10 PoE at/af incl.2 10GT EN50155 OS4 Managed PoE Ethernet Switch ;  
16.8V~56VDC dual input ; -40C~70C/-40F~158F ; IP21 housing w/ PoE galvanic isolation
- **TPGS-R6608XT-12-21-24TVI.....P/N: 8361-51812**  
8 10/100/1000T + 6 10G Copper M12 X-coded w/12 PoE at/af incl.4 10GT EN50155 OS4 Managed PoE Ethernet Switch ;  
16.8V~56VDC dual input ; -40C~70C/-40F~158F ; IP21 housing w/ PoE galvanic isolation
- **TGS-R6608XT-21-24TVI.....P/N: 8361-51832**  
8 10/100/1000T + 6 10G Copper M12 X-coded EN50155 OS4 Managed Ethernet Switch ; 16.8V~56VDC dual input ; -  
40C~70C/-40F~158F ; IP21 housing w/ galvanic isolation

## OPTIONAL ACCESSORIES

### Software package

Please refer to the [software datasheet](#)

### M12 Connector & Cable

#### Connector

- **ECONM12-04A(F)-C-180** 4 pin M12 (Female) A-coded 180 degree crimp type connector for power supply
- **ECONM12-08A(M)-180** 8 pin M12 (Male) A-coded 180 degree crimp type connector for reset/console/USB
- **ECONM12-05A(M)-C-180** 5 pin M12 (Male) A-coded 180 degree crimp type connector for DI/DO
- **ECONM12-08X(M)-SPEEDCON** 8 pin M12 (Male) X-coded 180 degree crimp type connector for data, Ethernet CAT6A (10G), shielded, SPEEDCON

#### Cable

- **ECONM12-4P(F)1.5M CABLE** 4 pin M12 (Female) A-coded 90 degree cable for power supply, 150cm
- **ECONM12-08M2-CONSOLE** 8 pin M12 (Male) A-coded 180 degree to RS232 cable for console, 150cm
- **ECABM12X83MSTP** 8 pin M12 (Male) X-coded 180 degree RJ45 STP cable for data, shielded, 300cm

#### Others

- **M12 to USB interface adapter** 8 pin M12 (Male) A-coded 180 degree M12 to USB 2.0 interface adapter, 8cm
- **USB 2.0 Ethernet Adapter** USB 2.0 to RJ45 Ethernet Adapter
- **ECONM12-08(M) TO DB9+USB2.0-1.5M CABLE** 8 pin M12 (Male) A-coded 180 degree M12 to USB2.0 to DB9 (Female) cable, 150cm

Lantech Communications Global Inc.  
www.lantechcom.tw  
info@lantechcom.tw

© 2023 Copyright Lantech Communications Global Inc. all rights reserved.  
The revise authority rights of product specifications belong to Lantech Communications Global Inc.  
In a continuing effort to improve and advance technology, product specifications are subject to change without notice.